

# Data sheet

sw-450.805

Push-handle dolly with tubular steel load surface



12  
years  
warranty

**External dimensions:**

Width:	785 mm	Construction:	steel, screwed
Depth:	450 mm	Colour:	RAL 5010 gentian blue / powder-coated
Height:	875 mm	Weight:	8,5 kg
Handle height:	860 mm	Load capacity:	150 kg

**Loading surface: (w/d)**

Material:	strut of tubular steel / powder-coated / RAL 5010 gentian blue
Bottom:	565 mm x 450 mm
Loading height:	185 mm

---

<b>Wheelset:</b>	Ø 125 x 30 mm, thermoplastic rubber, grey, non-marking 1 swivel castor (with brake) and 2 fixed castors deepgroove ball bearings More safety with the VARIOfit® foot protection
------------------	--

---

EAN-No.	4035694003989
Customs tariff no.	87168000
Country of origin:	European Community



# Data sheet

sw-450.805/AG

Push-handle dolly with tubular steel load surface , RAL 7016



## **External dimensions:**

Width:	785 mm	Construction:	steel, screwed
Depth:	450 mm	Colour:	RAL 7016 anthracite grey / powder-coated
Height:	875 mm	Weight:	8,5 kg
Handle height:	860 mm	Load capacity:	150 kg

## **Loading surface: (w/d)**

Material:	strut of tubular steel / powder-coated / RAL 7016 anthracite grey
Bottom:	615 mm x 415 mm
Loading height:	170 mm
Height of frame:	27 mm

---

<b>Wheelset:</b>	Ø 125 x 30 mm, electrically conductive thermoplastic rubber, non-marking 2 swivel castors with brakes and 2 fixed castors deepgroove ball bearings More safety with the VARIOfit® foot protection
------------------	--

---

EAN-No.	4035694077843
Customs tariff no.	87169090
Country of origin:	European Community

