

Data sheet



sw-810.014

Tipping unit for steel frame dolly



12
years
warranty

Outer dimensions:

Width: 1595 mm
Depth: 870 mm
Height: 700 mm
Weight: 58,5 kg

Inner dimensions:

Width: 1210 mm
Depth: 810 mm

Construction: steel, screwed
Colour: RAL 5010 gentian blue / powder-coated

- * robust welded steel construction
- * incl. location cups and lifting rings
- * tipping position approx. 18°
- * locking in the three basic positions by spring catch
(release the basic positions by pressing down the handle, the desired tilt position can be reached by swivelling the tipping unit and locked by releasing the handle)
- * additional tilt lock on handle
- * handle at both ends with red dipping caps
- * center of gravity of the loaded goods 450 mm

EAN-Nummer: 4035694071100
Customs tariff no: 87168000
Country of origin: European Community



Data sheet



sw-810.014/AG

Tipping unit for steel frame dolly, RAL 7016



Outer dimensions:

Width: 1595 mm
Depth: 870 mm
Height: 700 mm
Weight: 58,5 kg

Inner dimensions:

Width: 1210 mm
Depth: 810 mm

Construction: steel, screwed
Colour: RAL 7016 anthracite grey / powder-coated

- * robust welded steel construction
- * incl. location cups and lifting rings
- * tipping position approx. 18°
- * locking in the three basic positions by spring catch
(release the basic positions by pressing down the handle, the desired tilt position can be reached by swivelling the tipping unit and locked by releasing the handle)
- * additional tilt lock on handle
- * handle at both ends with red dipping caps
- * center of gravity of the loaded goods 450 mm

EAN-Nummer: 4035694082281
Customs tariff no: 87168000
Country of origin: European Community

