

# Data sheet

zu-1048

Industrial trailer with 2-axle turnable steering



**Outer dimensions:**

Width: 3310 mm  
Depth: 1500 mm  
Height: 700 mm  
Weight: 410 kg

**Inner dimensions:**

Width: 3000 mm  
Depth: 1500 mm

Construction: steel, fixed welded  
Colour: RAL 2004 pure orange / painted  
Load capacity: 5000 kg

Industrial trailer with 2-axle turnable steering

Loading surface: 3,000 x 1,500 mm (W/D)

Loading height: 700 mm

Created by:

\* extremely robust, puls-welded steel-section construction with rounded corners

\* 2-axle turnable steering

\* welded drawbar with retaining system, drawbar replaceable

\* standard or forged drawbar eye for 35 mm coupling bolts

\* compatible towing hitch height: 400 - 600 mm

ATTENTION: if the customer does not specify the height of the drawbar, we accept no liability for ease of coupling of the trailer

\* load surface of waterproof bonded plywood, surface finish screen printed, anti-slip

\* maximum speed: 6 km/h

Colour: pure orange RAL 2004, painted

Wheelset:

4 pcs. heavy duty pneumatic tyres of unbreakable welded steel construction, black, Ø 530 x 160 mm

Load capacity: 5,000 kg / static surface load

EAN-No. 4035694003231

---

**Wheelset:** Ø 530 x 160 mm, pneumatic tyre, black  
2-axle turnable steering

---

Customs tariff no: 87168000

Country of origin: European Community

